

MAESTRO YELLOW

Maestro Yellow Car Refinishing Product of two pack Polyester Steel Putty recommended for fast and efficient re-finishing. This product is recommended for all motor vehicles.



PRODUCT BENEFITS



FILL THE IMPERFECTIONS



POWERFUL FILLING



EASY SANDING



PIN HOLE FREE

PRODUCT FEATURES

WASHABILITY



✓ **BEST IN CLASS**
HIGH
MEDIUM
LOW

AVAILABLE PACKS



PREPARATION REQUIRED



Clean the surface, remove all dirt, grease, oil, wax with wax or grease remover. Make sure surface is clean and dry before start repairing.

APPLICATION

Using a plastic spreader, apply a thin layer of putty to surface, using a firm pressure for maximum adhesion.

Apply additional layers, building up damaged area higher than the surrounding surface to allow for sanding of the putty. Do not apply over fresh or uncured coatings.

When material has hardened, in approximately 15 minutes, sand over 100-180 grit sandpaper followed by 220-400 grit if desired.

FINISH



SMOOTH SHINY NORMAL LOW

✓ **SMOOTH**

TECHNICAL INFORMATION

- Coverage
120-140 sq.ft per Litre
- Application
Putty Knife
- Gel Time
3-5 minutes
- Sanding Time
15-20 minutes
- Induction
1k Primer and 2k Finish

MIXING

For best results, bring putty and provided hardener to room temperature. Place a 4" diameter puddle of putty on clean mixing surface; we recommend a non-absorbent plastic measure hardener 2% by weight. Mix thoroughly using a folding motion with a plastic spreader until uniform color is achieved. At room temperature (65°F) approximate setting time is 3-5 minutes.

SPREADING RATE



1 COAT
On previously painted surfaces to get the one coat hiding up to 140 sq.ft per liter/ per coat



2 COATS
On new surfaces up to 120 sq.ft per liter by two coats

SAFETY & ENVIRONMENTAL NOTES

Keep away from ignition sources because it is flammable. You must wear eye protection while applying paint. Always keep container air tight close. It must be kept out of children's reach. In case of contact with eyes, wash with brimful cup of water and immediately approach doctor. Always manage container to keep it in upright position. Protect it from extreme temperatures. Please do not empty into drain and water sources. Use of mask is advisable while rubbing down and same is true when applying by spray never breath vapor / spray. In case ventilation is insufficient the use of proper respiratory equipment is advised.