

SYNTHETIC METALLIC

PRODUCT BENEFITS







HIGH GLOSS



LEAD FREE



FAST DRYING




PRODUCT FEATURES

WASHABILITY



FINISH



SPREADING RATE



AVAILABLE PACKS



New surface must be clean, dry and free from efflorescent salts and grease. Level the surface with Master Knifing Filler. After rubbing down using a suitable abrasive paper use 1 coat of

Master Primer Red Oxide and allow to dry.

PREPARATION REQUIRED

TECHNICAL INFORMATION

Coverage

10-14 m² / litre / coat

Application

Spray Gun

Solvent

Petrol

Drying Time

6-8 hours between coats

No of Coats

2-3

Thinning

By Spray 20-25%

Cleaning

Clean all equipment with Petrol

TYPICAL SURFACES

New surfaces.

Previously painted surfaces.

SAFETY & ENVIRONMENTAL NOTES

You must wear eye protection while applying paint. Always keep container air tight close. It must be kept out of children's reach.

Incase of contact with eyes, wash with brimful cup of water and immediately approach doctor.

Always manage container to keep it in upright

position.
Protect it from extreme temperatures.
Please do not empty into drain and water sources.
Use of mask is advisable while rubbing down and same is true when applying by spray never breath vapor / spray.

In case ventilation is insufficient the use of proper

respiratory equipment is advised.

AFTER PREPARATION APPLY 2-3 COATS OF MASTER GLITTER METALLIC FINISH.







