

**POWDER COATING**

# MASTER HYBRID POWDER COATING

Best for corners and recessed area penetration.



## PRODUCT BENEFITS



WIDE RANGE




EXCELLENT GLOSS



CHEMICAL RESISTANT




INTERIOR DURABILITY



VOCs FREE

## PRODUCT FEATURES

### WASHABILITY



✓ BEST IN CLASS

HIGH

MEDIUM

LOW

### FINISH



SHINY

SMOOTH

NORMAL

LOW

✓ SMOOTH

### AVAILABLE PACKS



20 KG

## TECHNICAL INFORMATION

● Gloss

20 to 95 @ 60°

● Colour

No Restrictions

● Relative Humidity

60%

● Drying Time

10 min

● Pencil Hardness Test

H – 2H Pencil

● Adhesion

Cross-cut rating Gt0

● Resistance to neutral salt spray

No Blistering

● Temperature

200 °C

## PREPARATION REQUIRED



Pre-primed and smooth surface. Ensure that surface is clean, dry and clean from grease, oil and other contamination. Theoretical coverage and specific gravity is colour dependant



Thoroughly clean surface. Remove all defective or poorly adhering material by rubbing down using a suitable abrasive paper and dust off.

## SPREADING RATE



3 COATS

On new surfaces up to 200-180 degree Celsius for 10 to 12 minutes.

## SAFETY & ENVIRONMENTAL NOTES

Keep away from ignition sources because it is flammable. You must wear eye protection while applying paint. Always keep container air tight close. It must be kept out of children's reach. In case of contact with eyes, wash with brimful cup of water and immediately approach doctor. Always manage container to keep it in upright position. Protect it from extreme temperatures. Please do not empty into drain and water sources. Use of mask is advisable while rubbing down and same is true when applying by spray never breath vapor / spray. In case ventilation is insufficient the use of proper respiratory equipment is advised.

## DISCLAIMER

The technical and application properties contained in this data sheet were determined by the product chemistry. The actual results may vary with the colour and gloss level of each product.