

SUPER EMULSION

Master Superior Synthetic Enamel is a fabulous class synthetic enamel having no comparison in quality. It provides a tough smooth film which is washable and high resistant to mechanical wear. The composition of this paint is based on high quality long oil alkyd resin and long-lasting pigments.



PRODUCT BENEFITS



EXTRA COVERAGE



ANTI-FUNGAL



SUPREME QUALITY



LEAD FREE



ENVIRONMENT FRIENDLY

PRODUCT FEATURES

WASHABILITY



✓ BEST IN CLASS

HIGH

MEDIUM

LOW

AVAILABLE PACKS



0.91 Litre



3.64 Litre



14.56 Litre

PREPARATION REQUIRED



Surface must be clean, dry and free from efflorescent salts. After priming with Master Wall Primer, fill and smooth the surface with Master Wall Putty.



Remove all defective or poorly adhering material by rubbing down using a suitable abrasive paper and dust off. Spot prime and fill surface as described.




Make good minor defects. For large holes and cracks use sand and cement mixture. Allow to dry. Prime surface and then fill any surface imperfection with the filler described above. Allow to dry. Scuff surface using abrasive paper and dust off.

COLOURS AVAILABLE

50+

Factory Made Direct Shades



FINISH



SMOOTH SHINY NORMAL LOW

✓ SMOOTH

TECHNICAL INFORMATION

● Coverage

14-17 m² / liter / coat

● Application

Brush / Roller / Spray Gun

● Thinner

Clean Water

● Drying Time

1-2 hours between coats

● No of Coats

2-3

● Cleaning

Clean all equipment with Water

● Thinning

By Roller / Brush 50-75%
By Spray 25%

SPREADING RATE



2 COATS

On previously painted surfaces to get the one coat hiding up to 100sqft per liter/ per coat



3 COATS

On new surfaces up to 100 sq.ft per liter by two coats

TYPICAL SURFACES

- New surfaces.
- Previously painted surfaces.
- Powdery dusty surfaces. (With cracks and other surface defects)

SAFETY & ENVIRONMENTAL NOTES

Keep away from ignition sources because it is flammable. You must wear eye protection while applying paint. Always keep container air tight close. It must be kept out of children's reach. In case of contact with eyes, wash with brimful cup of water and immediately approach doctor. Always manage container to keep it in upright position. Protect it from extreme temperatures. Please do not empty into drain and water sources. Use of mask is advisable while rubbing down and same is true when applying by spray never breath vapor / spray. In case ventilation is insufficient the use of proper respiratory equipment is advised.