
ROOF MASTER

Roof Master is high build water based Elastomeric roof paint. Roof Master is designed to protect masonry surfaces. It protects your surfaces from wind, driven rain and can create a water proof system if applied correctly. It helps to maintain interior temperature upto 10* by resisting extreme hot or cold weather.

PRODUCT BENEFITS







HIGH BUILD



UV RAYS RESISTANT



PRODUCT FEATURES


WASHABILITY



FINISH



SPREADING RATE



PREPARATION REQUIRED



Surface must be clean, dry and free from efflorescent salts. After priming with Master Wall Primer, fill and smooth the surface with Master Wall Putty.

AVAILABLE PACKS





16 Litres

TYPICAL SURFACES

- New surfaces.
- Previously painted surfaces.
- Powdery dusty surfaces. (With cracks and other surface defects)

SAFETY & ENVIRONMENTAL NOTES

Thoroughly clean surface. Remove all defective or poorly adhering material by rubbing down using a suitable abrasive paper and dust off. Prime with Master Wall Sealer and prepare the base with Master Wall Putty where needed.

TECHNICAL INFORMATION

Coverage

34-36 Square feet / litre / coat

Application

Brush / Roller

Thinner

Clean Water

Drying Time / Recoat Time

2-3 hours / 24 hours between coats

Cleaning

Clean all equipment with Water

No. of Coats

Keep away from ignition sources because it is flammable.

You must wear eye protection while applying paint. Always keep container air tight close.

It must be kept out of children's reach.

Incase of contact with eyes, wash with brimful cup of water and immediately approach doctor.

Always manage container to keep it in upright position.

Protect it from extreme temperatures.

Please do not empty into drain and water sources. Use of mask is advisable while rubbing down and same is true when applying by spray never breath vapor / spray.

In case ventilation is insufficient the use of proper respiratory equipment is advised.

STIR THOROUGHLY BEFORE USE.